

DuploMED® 22260

Single-sided acrylic tape with foam carrier



Diagnostic



Electrodes



Wound Care



Surgical



Ostomy



Consumer
Healthcare



Wearables



Product construction

	Name	Colour	Thickness (µm / mil) *
Liner	Film (Polyethylene terephthalate)	transparent	50 / 2
Adhesive closed side	Pure acrylic	transparent	450 / 17.7
Carrier	Foam (Polyethylene)	beige	
Total thickness			500 / 19.7

Main application fields

- Closure systems for ostomy bags
- Applications requiring top cushioning
- Attachment of medical devices to skin

Product advantages / Features and Benefits

- Excellent conformability
- Good bonding strength on skin up to three days
- Good adhesion to plastic components
- Easy liner release to enable automated production processes

Standard technical data **

Peel strength 90°	on POM, at 23 ± 2 °C (73.4 ± 3.6 °F)	9	N/25 mm	32	oz/in
Elongation	according to DIN EN 29073-3 MD			260 %	
	according to DIN EN 29073-3 CD			440 %	
Tensile strength	according to DIN EN 29073-3 MD	13	N/15 mm	47	oz/0.6 in
	according to DIN EN 29073-3 CD	9	N/15 mm	32	oz/0.6 in
Peel strength 180°	on stainless steel at 23 ± 2 °C (73.4 ± 3.6 °F)	35	N/25 mm	126	oz/in

Technical data foam

Material	Foam (Polyethylene)
Colour	beige
Density (acc. ISO-845)	95 kg/m ³

* Typical values, not intended to be used as product specifications

** Specific test results, statistically approved

DuploMED® 22260

Biocompatibility and safety

Customers should perform their own assessment to ensure the final product is in compliance with all applicable Medical Device regulatory requirements. To support the assessment, and upon request, Lohmann can provide, where available, biocompatibility testing results (ISO10993) specific to either the product supplied by Lohmann or its' constituent components.

Application condition

Recommended temperature for all conventional processing 20 °C to 30 °C (68 °F to 86 °F)

Recommended application temperature 18 °C to 35 °C (64.4 °F to 95 °F)

Application guidelines www.lohmann-tapes.com

Storage and shelf-life

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).

When properly stored the shelf-life of the product is at least 2 years after delivery.

Product presentation

Converted product	Rolls	Spools
Width [mm / in]	on request	
Length [m / yd]	on request	
Max. log width [mm / in]:	1260 / 49.6	Other dimensions, die-cuts and sheets on request.

Sheet




Roll




Spool



Die Cut



Pick & Place



IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: March 2024

Lohmann GmbH & Co. KG
 Irlicher Straße 55 / 56567 Neuwied / Germany
 medical@lohmann-tapes.com / www.lohmann-tapes.com